

IR Dome Camera

Weather-proof IR Dome Camera

DFC212. 212H



- 1/3" SONY CCD
- 420 / 700 TV Lines Resolution
- 4.3mm Board Lens
- Multiple-angled Lens for Optimum Night View
- 15M Effective Distance (18 LED)
- Photodiode Design for Accurate IR Activation
- Double Glass to Reduce Internal Reflection
- Aluminum Housing for Better Heat Dissipation
- IP66 for Weather Proof Application

SPECIFICATION

Model	DFC212	DFC212H
Pick Up Device	1/3" SONY CCD	
Effective Pixels	NTSC: 510 (H) x 492 (V)	NTSC: 976 (H) x 494 (V)
	PAL: 500 (H) x 582 (V)	PAL: 976 (H) x 582 (V)
Resolution	420 TV lines	700 TV lines
Lens mechanism	3 Axis	
Synchronizing System	Internal Sync.	
Scanning System	2:1 Interlace	
S/N Ratio	More than 48 dB(AGC OFF)	
Electronic Shutter	Auto : 1/60 (1/50) ~1/100,000 sec / Flk	
Min. Illumination	0.1 Lux Color / F2.0 (50IRE)	
Video Output	1.0Vp-p / 75 ohm composite	
Lens Type	4.3mm Board Lens	
IR Distance	15M (18pcs IR LED)	
IR Trigger	2.6 Lux / 2.7 Lux (IR ON / OFF)	
Auto White Balance	2400° ~ 9400°k	
Power Source	DC12V ± 10% 1A	
Power Consumption	2.8W (Max)	
Current	240mA (Max)	
Weight	N.W./G.W.: 0.32kg / 0.38kg	
Dimension	70 (H) x 94 (Diameter) mm	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)	
Storage Temperature	-20°C ~ 70°C (-4°F ~ 158°F)	
Weather Proof	IP66	

Dimension

Unit : mm

