

H.264 DVR

8CH 3G Network DVR

DFH1008. 1008D



- H.264 Compression for Recording & Network
- Triplex for Recording, Playback and Network
- Supports D1 / HD1 / CIF Resolutions
- Supports Real-time Playback @ CIF
- Supports 100% Independent Network
- 3G Mobile Surveillance (iPhone / Window Mobile / Symbian / Blackberry / Google Phone).
- Mouse-control GUI (32 bit True Color)
- Supports CMS up to 256 Cameras
- Support Touch Panel Function
- Support VGA Output for 1920 x 1080
- Support IR Remote Control / USB Mouse Control
- Supports 16 Languages
- Resolution & FPS Setup by Each Channel

SPECIFICATION

Model	DFH1008. 1008D
Operating System	Embedded Linux
Mode	Pentaplexer (Live / Recording / Playback / Network / Backup)
Video Compression	H.264
Video System	NTSC / PAL
Video Input	BNC x 8 (Composite / 75Ω Balanced)
Video Output	Main Monitor x 1 / Spot Monitor x 1 / VGA Output x 1 (1920 x 1080)
Audio Input	RCA x 4
Audio Output	RCA x 1
Audio Backup	YES
Network Audio	Live and Playback
Audio Compression	G.711
Alarm Input	Input x 8
Alarm Output	Output x 1
Display Resolution	NTSC: D1 (720 x 480) / PAL: D1 (704 x 576)
Display Frame Rate	NTSC: 240fps / PAL: 200fps
Display Mode	Digital Zoom / PIP / Auto SEQ / Motion Pop-up
Recording Compression	H.264
Recording Resolution	NTSC: D1 (720 x 480) / HD1 (360 x 480) / CIF (360 x 240) PAL: D1 (720 x 576) / HD1 (720 x 576) / CIF (352 x 288)
Recording Frame Rate	NTSC: 60fps @ D1 / 120fps @ HD1 / 240fps @ CIF PAL: 50fps @ D1 / 100fps @ HD1 / 200fps @ CIF
Recording Quality	5 Levels (Highest / High / Normal / Low / Lowest)
Recording Mode	Auto / Manual / Motion / Schedule / Alarm
Recording Setup	Adjustable Resolution and FPS by Each Channel
Playback Mode	1 / 4 / 8 Channels
Playback Resolution	NTSC: D1 (720 x 480) / HD1 (720 x 240) / CIF (360 x 240) PAL: D1 (720 x 576) / HD1 (720 x 288) / CIF (352 x 288)
Playback Frame Rate	NTSC: 60fps @ D1 / 120fps @ HD1 / 240fps @ CIF PAL: 50fps @ D1 / 100fps @ HD1 / 200fps @ CIF
Playback Speed	Normal / REW / FF (2X ~ 64X) / Pause / SF (1/2 ~ 1/8X)
Search Mode	Date / Time / Motion / Alarm / Camera
Watermark	Support Watermark
Internal HDD	SATA / SATAII HDD x 2 (2TB max.)
Backup Mode	USB / Network / External USB DVD-RW / Built-in DVD-RW (1008D Only)
GUI	32bit True Color GUI
Multi-Language	16 Languages
IR Remote Control	YES
USB Mouse Control	YES
PTZ	PELCO-P / PELCO-D / LILIN / SAMSUNG / LG
Ethernet	RJ45, 10/100/1000 Base-T
Network Service	TCP/IP, DHCP, PPPoE (ADSL), LAN, DDNS
Mobile Surveillance	YES (3G/GPRS) – Symbian, Windows Mobile, JAVA, iPhone, Blackberry, Android
Network Access Mode	IE / AP / CMS (free software)
Motion Detection	YES (12 x 16 Grids per channel)
Pre-alarm	10 sec
Post-alarm	10 ~ 60 sec
Power Input	DC 12V / 5A
Working Temperature	5°C ~ 40°C (41°F ~ 104°F)
Working Humidity	Less than 90%
Dimension	430 x 293 x 55 (mm)
Weight	3 Kg (N.W)
Certificates	CE / FCC / RoHS / WEEE

Dimension

